

Standard Duty Emergency Stop Switches-Types: ESL-SS 4 pole & ATEX

IDEM Standard Duty Emergency Stop Switches are designed to provide robust Emergency Stop protection for exposed conveyors or machines.

Stainless Steel 316 housings (IP69K)

Conformance to ISO 13850, IEC 947-5-1 and IEC 947-5-5

A special lid safety trip mechanism means that the safety contacts will open if the lid is removed.

Button protection shroud version with Padlock holes for 'Lock off' during maintenance.

Optional 2 colour LED



Type ESL-SS (Stainless Steel)



Type ESL-SS(P) (Stainless Steel) with protection shroud and padlock holes



Type ESL-SS(LP) (Stainless Steel) with 2 colour LED and protection shroud



Type ESL-SS(L) (Stainless Steel) with 2 colour LED

Sales Number	Type	Conduit Entry	Contacts
232001	ESL-SS	M20	2NC 2NO
232002	ESL-SS	1/2" NPT	2NC 2NO
232003	ESL-SS	M20	3NC 1NO
232004	ESL-SS	1/2" NPT	3NC 1NO
232005	ESL-SS	M20	4NC
232006	ESL-SS	1/2" NPT	4NC
232007	ESL-SS	EX 3m.	1NC 1NO
232008	ESL-SS	EX 3m.	2NC
232029	ESL-SS	EX 3m.	2NC 2NO

Sales Number	Type	Conduit Entry	Contacts
232009	ESL-SS(P)	M20	2NC 2NO
232010	ESL-SS(P)	1/2" NPT	2NC 2NO
232011	ESL-SS(P)	M20	3NC 1NO
232012	ESL-SS(P)	1/2" NPT	3NC 1NO
232013	ESL-SS(P)	M20	4NC
232014	ESL-SS(P)	1/2" NPT	4NC
232015	ESL-SS(P)	EX 3m.	1NC 1NO
232016	ESL-SS(P)	EX 3m.	2NC
232030	ESL-SS(P)	EX 3m.	2NC 2NO

Sales Number	Type	Conduit Entry	Contacts
232017	ESL-SS(L)	M20	2NC 2NO
232018	ESL-SS(L)	1/2" NPT	2NC 2NO
232019	ESL-SS(L)	M20	3NC 1NO
232020	ESL-SS(L)	1/2" NPT	3NC 1NO
232021	ESL-SS(L)	M20	4NC
232022	ESL-SS(L)	1/2" NPT	4NC
232023	ESL-SS(LP)	M20	2NC 2NO
232024	ESL-SS(LP)	1/2" NPT	2NC 2NO
232025	ESL-SS(LP)	M20	3NC 1NO
232026	ESL-SS(LP)	1/2" NPT	3NC 1NO
232027	ESL-SS(LP)	M20	4NC
232028	ESL-SS(LP)	1/2" NPT	4NC

For LED models add voltage code to Sales Number

Steady Green / Flashing Red
A - 24Vdc B - 110Vac C - 230V.ac

Steady Green / Steady Red
AS-24Vdc BS-110Vac CS-230V.ac

Standards: IEC 947-5-1 IEC947-5-5 EN954-1 EN62061
UL508 ISO13850 ISO13849-1

Safety Classification and Reliability Data:

Mechanical Reliability B10d
EN 954-1
ISO 13849-1
EN 62061

Safety Data - Annual Usage
PFHd
Proof Test Interval (Life)
MTTFd
Enclosure / Cover
IP Rating
IP67 IP69K
Mounting
4 x M5
Mounting position
Any
Conduit entries
3 x M20 or 3 x 1/2" NPT by part number
Torque settings
Mounting M5 4.0 Nm
Lid T20 Torx M4 1.5 Nm
Terminals 1.0 Nm

Ambient Temperature
-25C. 80 C.
Vibration resistance
10-500Hz 0.35mm
Shock resistance
15g 11ms
Weight
820 g.
Contact type
IEC 947-5-1 Double break Type Zb
Snap Action up to 4NC (positive break)
2NO (Auxiliary)

Contact Material
Silver
Termination
Clamp up to 2.5 sq. mm conductors
Rating
Utilisation Category : AC15
Operational Rating
240V. 3A.
Thermal Current (Ith)
10A.
Rated Insulation Voltage (Ui)
500V.
Withstand Voltage (Uimp)
2500V.
Short Circuit Overload Protection
Fuse Externally 10A. (FF)

Classification Exd IIC T6 (Ta -20 to +60C.) Gb
Ex tb IIIC T85C. (-20 to +60C.) Db

